

UNIVERSAL BEAMS - AS/NZS GRADE 300

| Description | Depth of section | Width of section | Weight (KG/M) | Flange thickness | Web thickness |
|-------------|------------------|------------------|---------------|------------------|---------------|
| 150 UB 14 | 150 mm | 75 mm | 14.000 | 7 mm | 5 mm |
| 150 UB 18 | 155 mm | 75 mm | 18.000 | 9.5 mm | 6 mm |
| 180 UB 16 | 173 mm | 90 mm | 16.100 | 7 mm | 4.5 mm |
| 180 UB 18 | 175 mm | 90 mm | 18.100 | 8 mm | 5 mm |
| 180 UB 22 | 179 mm | 90 mm | 22.200 | 10 mm | 6 mm |
| 200 UB 18 | 198 mm | 99 mm | 18.200 | 7 mm | 4.5 mm |
| 200 UB 22 | 202 mm | 133 mm | 22.300 | 7 mm | 5 mm |
| 200 UB 25 | 203 mm | 133 mm | 25.400 | 7.8 mm | 5.8 mm |
| 200 UB 29 | 207 mm | 134 mm | 29.800 | 9.6 mm | 6.3 mm |
| 250 UB 25 | 248 mm | 124 mm | 25.700 | 8 mm | 5 mm |
| 250 UB 31 | 252 mm | 146 mm | 31.400 | 8.6 mm | 6.1 mm |
| 250 UB 37 | 256 mm | 146 mm | 37.300 | 10.9 mm | 6.4 mm |
| 310 UB 32 | 298 mm | 149 mm | 32.000 | 8 mm | 5.5 mm |
| 310 UB 40 | 304 mm | 165 mm | 40.400 | 10.2 mm | 6.1 mm |
| 310 UB 46 | 307 mm | 166 mm | 46.200 | 11.8 mm | 6.7 mm |
| 360 UB 45 | 352 mm | 171 mm | 44.700 | 9.7 mm | 6.9 mm |
| 360 UB 51 | 356 mm | 171 mm | 50.700 | 11.5 mm | 7.3 mm |
| 360 UB 57 | 359 mm | 172 mm | 56.700 | 13 mm | 8 mm |
| 410 UB 54 | 403 mm | 178 mm | 53.700 | 10.9 mm | 7.6 mm |
| 410 UB 60 | 406 mm | 178 mm | 59.700 | 12.8 mm | 7.8 mm |
| 460 UB 67 | 454 mm | 190 mm | 67.100 | 12.7 mm | 8.5 mm |
| 460 UB 74 | 457 mm | 190 mm | 74.600 | 14.5 mm | 9.1 mm |
| 460 UB 82 | 460 mm | 191 mm | 82.100 | 16 mm | 9.9 mm |
| 530 UB 82 | 528 mm | 209 mm | 82.000 | 13.2 mm | 9.6 mm |
| 530 UB 92 | 533 mm | 209 mm | 92.400 | 15.6 mm | 10.2 mm |
| 610 UB 101 | 602 mm | 228 mm | 101.000 | 14.8 mm | 10.6 mm |
| 610 UB 113 | 607 mm | 228 mm | 113.000 | 17.3 mm | 11.2 mm |
| 610 UB 125 | 612 mm | 229 mm | 125.000 | 19.6 mm | 11.9 mm |